



*GenTent® Installation Addendum for  
Generac XT8000E / XT8000EFI / XT8500EFI models*

Generac recently changed the size of their frame and the electric panel for this model. In order to attach the GenTent®, you will slightly adjust installation for one corner attachment.

The adjustment will be for one clamp which connects under the left-hand side of your electric panel, where the electric panel cuts down very low (under the Generac logo) in the even the clamp & rubber sleeve will not fit properly (Fig. A)



Fig. A

1. Remove the bolt on the back /bottom of that panel. (Fig. B)
2. Pull the electric panel forward, and slide the rubber sleeve onto the vertical post with the opening out. (Fig. C & Fig. D)
3. Slide clamp over the vertical frame post, then slide clamp up and under the loose electric panel. (Fig. E)
4. Mount the clamp at a 45-degree angle. (Fig. F)
5. Re-fasten your generator electric panel and bolt. (Fig. B)



Fig. D.



Fig. E



Fig. F

**TOOLS NEEDED:**  
13mm open end, box, or socket wrench

**INSTALLATION OVERVIEW:**  
The process should take approximately 5 minutes:

**Install GenTent Clamps:** Under front left panel and remaining as normal.  
**Install GenTent Frame:** As normal.  
**Install GenTent Canopy:** As normal.

Fig B.



Fig. C



The remaining clamps and GenTent® Installation will continue along the steps of the standard GenTent® Installation Manual.

For additional assistance, questions, or follow up please contact GenTent® Safety Canopies Customer Care:

Tel: 781-334-8368 extension 1

E-mail: [customercare@gentent.com](mailto:customercare@gentent.com)